

**INBUILT PULLER**

Capacity: 5-50 ton.

Max. Reach: 140-250 mm.

Max. Spread: 200-500 mm.

**FEATURES**

- Inbuilt Safety Relief Valve prevents Accidental Over pressurization of the puller.
- 360 degree rotary handle Swivel Clevis allows pumping from all directions.
- Spring loaded live centering cone allows easy centering of puller on shaft.
- Complete hydraulic puller allows effortless generation of force and dismounting.
- Bright chrome finish on jaws and head to resist corrosion.
- 5, 10 & 20 ton sets are supplied in a plastic carrying case, 30 & 50 ton sets are supplied in a robust wooden box.
- 6, 2 and 3 jaw combination puller cross head for variety of applications.
- The jaws are made of high strength, heat treated steel alloy for safety and durability.
- Light weight, compact, safe and easy to carry. one man operation & is best suited for all industries.



Model No.	Output Capacity	Stroke	Jaw No.	Max. Spread A	Max. Reach B	Thickness of Jaw C	Thickness of Jaw Tip D	Height H	Weight
	(Ton)	(mm)		(mm)	(mm)	(mm)	(mm)	(mm)	(kg)
AIB-5	5	50	3	200	140	26	11	400	7.6
AIB-10	10	60	3	250	170	30	13	500	10.1
AIB-20	20	70	3	350	205	33	18	580	18.6
AIB-30	30	70	3	400	220	35	20	610	24.2
AIB-50	50	60	3	500	250	40	25	620	42.9

Model No.	Output Capacity	Stroke	Max. Spread A	Max. Reach B	Thickness of Jaw C	Thickness of Jaw Tip D	Height H	Weight
	(Ton)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(kg)
AIBC-5	5	50	200	166	140	15	480	13.8
AIBC-10	10	60	300	204	170	16	510	15.1
AIBC-20	20	70	400	238	205	16	570	20.4